


# GV7AU387

Voltage release, TeSys GV5 GV6 GV7, MN  
undervoltage trip, 380-440V AC 50/60Hz

Product availability : Non-Stock - Not normally stocked in distribution facility



❗ Discontinued

GV7AU387 has not been replaced. Please contact your customer care center for more information.

## Main

|                           |                                     |
|---------------------------|-------------------------------------|
| Range                     | TeSys                               |
| Product or component type | Undervoltage trip                   |
| Device short name         | GV7AS                               |
| Device application        | Control                             |
| Range compatibility       | TeSys GV5<br>TeSys GV6<br>TeSys GV7 |

## Complementary

|                                 |                                                                                                                                                                                                                                                                       |
|---------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| [Uc] control circuit voltage    | 380...440 V AC 50/60 Hz                                                                                                                                                                                                                                               |
| Control circuit voltage limits  | 0.85...1.1 Un                                                                                                                                                                                                                                                         |
| [Ui] rated insulation voltage   | 690 V AC IEC 60947-1<br>600 V AC UL 508<br>600 V AC CSA C22.2 No 14                                                                                                                                                                                                   |
| Threshold tripping voltage      | 0.35...0.7 Ue                                                                                                                                                                                                                                                         |
| Inrush power in VA              | 10 VA AC                                                                                                                                                                                                                                                              |
| Hold-in power consumption in VA | 5 VA AC                                                                                                                                                                                                                                                               |
| Operating time                  | < 50 ms IEC 60947-1                                                                                                                                                                                                                                                   |
| On-load factor                  | 100 %                                                                                                                                                                                                                                                                 |
| Connections - terminals         | screw clamp terminals 1 0.00 in <sup>2</sup> (1 mm <sup>2</sup> )flexible with cable end<br>screw clamp terminals 1 0.00 in <sup>2</sup> (1.5 mm <sup>2</sup> )flexible without cable end<br>screw clamp terminals 1 0.00 in <sup>2</sup> (1.5 mm <sup>2</sup> )solid |
| Tightening torque               | 1.2 N.m screw clamp terminals                                                                                                                                                                                                                                         |
| Net weight                      | 0.23 lb(US) (0.105 kg)                                                                                                                                                                                                                                                |
| Quantity per set                | Set of 10                                                                                                                                                                                                                                                             |

## Ordering and shipping details

|                   |                                    |
|-------------------|------------------------------------|
| Category          | 22366 - MAN STR PROTECTORS-GV1/GV3 |
| Discount Schedule | I11                                |
| GTIN              | 00785901617501                     |
| Returnability     | No                                 |
| Country of origin | FR                                 |

## Offer Sustainability

|                            |                                                                                                                                                                                                                                                                   |
|----------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| California proposition 65  | WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide which is known to the State of California to cause Carcinogen harm. For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a> |
| REACH free of SVHC         | Yes                                                                                                                                                                                                                                                               |
| EU RoHS Directive          | Compliant<br><a href="#">EU RoHS Declaration</a>                                                                                                                                                                                                                  |
| Toxic heavy metal free     | Yes                                                                                                                                                                                                                                                               |
| Mercury free               | Yes                                                                                                                                                                                                                                                               |
| RoHS exemption information | <a href="#">Yes</a>                                                                                                                                                                                                                                               |
| China RoHS Regulation      | <a href="#">China RoHS declaration</a><br>Pro-active China RoHS declaration (out of China RoHS legal scope)                                                                                                                                                       |
| WEEE                       | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.                                                                                                                                      |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|