



Main

Range	TeSys
Device short name	LA1LD
Product or component type	Interface module
Range compatibility	TeSys Integral contactor breaker

Complementary

Output type	Relay output
Mounting location	On top of the integral unit
[Uc] control circuit voltage	24 V DC
Control circuit voltage limits	0.85...1.1 Uc DC
Connections - terminals	Screw clamp terminal 1 cable(s) 1 mm ² Screw clamp terminal 2 cable(s) 2.5 mm ²
[Ue] rated operational voltage	24...240 V AC 50/60 Hz
Net weight	0.11 kg

Environment

[Ith] conventional free air thermal current	63 A
Protection type	Overvoltage protection Against reverse polarity
IP degree of protection	IP20 B conforming to IEC 60529
Ambient air temperature for operation	-25...50 °C
Ambient air temperature for storage	-25...70 °C

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information

WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
------	---

Contractual warranty

Warranty	18 months
----------	-----------