



## Main

|                                             |                                                                                                                                                                                                                                                                                              |
|---------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Range                                       | TeSys                                                                                                                                                                                                                                                                                        |
| Product name                                | TeSys D                                                                                                                                                                                                                                                                                      |
| Product or component type                   | Contactor                                                                                                                                                                                                                                                                                    |
| Device short name                           | LC1D                                                                                                                                                                                                                                                                                         |
| Contactor application                       | Resistive load                                                                                                                                                                                                                                                                               |
| Utilisation category                        | AC-1                                                                                                                                                                                                                                                                                         |
| Poles description                           | 4P                                                                                                                                                                                                                                                                                           |
| Power pole contact composition              | 4 NO                                                                                                                                                                                                                                                                                         |
| [Ue] rated operational voltage              | Power circuit: $\leq 690$ V AC 25...400 Hz<br>Power circuit: $\leq 300$ V DC                                                                                                                                                                                                                 |
| [Ie] rated operational current              | 25 A (at $\leq 60$ °C) at $\leq 440$ V AC AC-1 for power circuit                                                                                                                                                                                                                             |
| Control circuit type                        | AC at 50/60 Hz                                                                                                                                                                                                                                                                               |
| [Uc] control circuit voltage                | 110 V AC 50/60 Hz                                                                                                                                                                                                                                                                            |
| Auxiliary contact composition               | 1 NO + 1 NC                                                                                                                                                                                                                                                                                  |
| [Uimp] rated impulse withstand voltage      | 6 kV conforming to IEC 60947                                                                                                                                                                                                                                                                 |
| Overvoltage category                        | III                                                                                                                                                                                                                                                                                          |
| [Ith] conventional free air thermal current | 10 A (at $60$ °C) for signalling circuit<br>25 A (at $60$ °C) for power circuit                                                                                                                                                                                                              |
| Irms rated making capacity                  | 140 A AC for signalling circuit conforming to IEC 60947-5-1<br>250 A DC for signalling circuit conforming to IEC 60947-5-1<br>250 A at 440 V for power circuit conforming to IEC 60947                                                                                                       |
| Rated breaking capacity                     | 250 A at 440 V for power circuit conforming to IEC 60947                                                                                                                                                                                                                                     |
| [Icw] rated short-time withstand current    | 30 A $40$ °C - 10 min for power circuit<br>61 A $40$ °C - 1 min for power circuit<br>105 A $40$ °C - 10 s for power circuit<br>210 A $40$ °C - 1 s for power circuit<br>100 A - 1 s for signalling circuit<br>120 A - 500 ms for signalling circuit<br>140 A - 100 ms for signalling circuit |
| Associated fuse rating                      | 10 A gG for signalling circuit conforming to IEC 60947-5-1<br>40 A gG at $\leq 690$ V coordination type 1 for power circuit                                                                                                                                                                  |

|                               |                                                                                                                                                                                                                                                                                                                                                                |
|-------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                               | 25 A gG at ≤ 690 V coordination type 2 for power circuit                                                                                                                                                                                                                                                                                                       |
| Average impedance             | 2.5 mOhm - Ith 25 A 50 Hz for power circuit                                                                                                                                                                                                                                                                                                                    |
| [Ui] rated insulation voltage | Power circuit: 600 V CSA certified<br>Power circuit: 600 V UL certified<br>Signalling circuit: 690 V conforming to IEC 60947-1<br>Signalling circuit: 600 V CSA certified<br>Signalling circuit: 600 V UL certified<br>Power circuit: 690 V conforming to IEC 60947-4-1                                                                                        |
| Electrical durability         | 0.8 Mcycles 25 A AC-1 at Ue ≤ 440 V                                                                                                                                                                                                                                                                                                                            |
| Power dissipation per pole    | 1.56 W AC-1                                                                                                                                                                                                                                                                                                                                                    |
| Safety cover                  | With                                                                                                                                                                                                                                                                                                                                                           |
| Mounting support              | Rail<br>Plate                                                                                                                                                                                                                                                                                                                                                  |
| Standards                     | CSA C22.2 No 14<br>EN 60947-4-1<br>EN 60947-5-1<br>IEC 60947-4-1<br>IEC 60947-5-1<br>UL 508                                                                                                                                                                                                                                                                    |
| Product certifications        | LROS (Lloyds register of shipping)<br>DNV<br>GOST<br>UL<br>GL<br>BV<br>RINA<br>CSA<br>CCC                                                                                                                                                                                                                                                                      |
| Connections - terminals       | Control circuit: lugs-ring terminals (external diameter: 8 mm)<br>Power circuit: lugs-ring terminals (external diameter: 8 mm)                                                                                                                                                                                                                                 |
| Tightening torque             | Control circuit: 1.7 N.m - on lugs-ring terminals - with screwdriver flat Ø 6 mm M3.5<br>Control circuit: 1.7 N.m - on lugs-ring terminals - with screwdriver Philips No 2 M3.5<br>Power circuit: 1.7 N.m - on lugs-ring terminals - with screwdriver flat Ø 6 mm M3.5<br>Power circuit: 1.7 N.m - on lugs-ring terminals - with screwdriver Philips No 2 M3.5 |
| Operating time                | 4...19 ms opening<br>12...22 ms closing                                                                                                                                                                                                                                                                                                                        |
| Safety reliability level      | B10d = 1369863 cycles contactor with nominal load conforming to EN/ISO 13849-1<br>B10d = 20000000 cycles contactor with mechanical load conforming to EN/ISO 13849-1                                                                                                                                                                                           |
| Mechanical durability         | 15 Mcycles                                                                                                                                                                                                                                                                                                                                                     |
| Maximum operating rate        | 3600 cyc/h 60 °C                                                                                                                                                                                                                                                                                                                                               |

## Complementary

|                                 |                                                                                                                                                  |
|---------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------|
| Coil technology                 | Without built-in suppressor module                                                                                                               |
| Control circuit voltage limits  | Drop-out: 0.3...0.6 Uc AC 50/60 Hz (at 60 °C)<br>Operational: 0.8...1.1 Uc AC 50 Hz (at 60 °C)<br>Operational: 0.85...1.1 Uc AC 60 Hz (at 60 °C) |
| Inrush power in VA              | 70 VA 60 Hz cos phi 0.75 (at 20 °C)<br>70 VA 50 Hz cos phi 0.75 (at 20 °C)                                                                       |
| Hold-in power consumption in VA | 7.5 VA 60 Hz cos phi 0.3 (at 20 °C)<br>7 VA 50 Hz cos phi 0.3 (at 20 °C)                                                                         |
| Heat dissipation                | 2...3 W at 50/60 Hz                                                                                                                              |
| Auxiliary contacts type         | type mechanically linked 1 NO + 1 NC conforming to IEC 60947-5-1<br>type mirror contact 1 NC conforming to IEC 60947-4-1                         |
| Signalling circuit frequency    | 25...400 Hz                                                                                                                                      |
| Minimum switching current       | 5 mA for signalling circuit                                                                                                                      |
| Minimum switching voltage       | 17 V for signalling circuit                                                                                                                      |
| Non-overlap time                | 1.5 ms on de-energisation between NC and NO contact<br>1.5 ms on energisation between NC and NO contact                                          |
| Insulation resistance           | > 10 MOhm for signalling circuit                                                                                                                 |

## Environment

|                         |                                         |
|-------------------------|-----------------------------------------|
| IP degree of protection | IP20 front face conforming to IEC 60529 |
|-------------------------|-----------------------------------------|

|                                                       |                                                                                                                                                                                    |
|-------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Protective treatment                                  | TH conforming to IEC 60068-2-30                                                                                                                                                    |
| Pollution degree                                      | 3                                                                                                                                                                                  |
| Ambient air temperature for operation                 | -5...60 °C                                                                                                                                                                         |
| Ambient air temperature for storage                   | -60...80 °C                                                                                                                                                                        |
| Permissible ambient air temperature around the device | -40...70 °C at U <sub>c</sub>                                                                                                                                                      |
| Operating altitude                                    | 3000 m without                                                                                                                                                                     |
| Fire resistance                                       | 850 °C conforming to IEC 60695-2-1                                                                                                                                                 |
| Flame retardance                                      | V1 conforming to UL 94                                                                                                                                                             |
| Mechanical robustness                                 | Vibrations contactor open: 2 Gn, 5...300 Hz<br>Vibrations contactor closed: 4 Gn, 5...300 Hz<br>Shocks contactor closed: 15 Gn for 11 ms<br>Shocks contactor open: 10 Gn for 11 ms |
| Height                                                | 85 mm                                                                                                                                                                              |
| Width                                                 | 45 mm                                                                                                                                                                              |
| Depth                                                 | 92 mm                                                                                                                                                                              |
| Net weight                                            | 0.365 kg                                                                                                                                                                           |

### Offer Sustainability

|                            |                                                                                                                             |
|----------------------------|-----------------------------------------------------------------------------------------------------------------------------|
| Sustainable offer status   | Green Premium product                                                                                                       |
| REACH Regulation           | <a href="#">REACH Declaration</a>                                                                                           |
| REACH free of SVHC         | Yes                                                                                                                         |
| EU RoHS Directive          | Compliant<br><a href="#">EU RoHS Declaration</a>                                                                            |
| Toxic heavy metal free     | Yes                                                                                                                         |
| Mercury free               | Yes                                                                                                                         |
| RoHS exemption information | <a href="#">Yes</a>                                                                                                         |
| China RoHS Regulation      | <a href="#">China RoHS declaration</a>                                                                                      |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>                                                                               |
| Circularity Profile        | <a href="#">End of Life Information</a>                                                                                     |
| WEEE                       | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |

### Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|