



Main

Product or component type	DC choke
Range compatibility	Altivar 61 Altivar 71
Device application	Reduction of current harmonics
Value of inductance	0.52 mH
[In] rated current	84.5 A
Thermal losses	98.3 W
Product compatibility	ATV61HD11M3X ATV61HD15M3X ATV61HD22N4 ATV61HD30N4 ATV61HD37N4 ATV71HD11M3X ATV71HD15M3X ATV71HD22N4 ATV71HD30N4 ATV71HD37N4 ATV71WD22N4 ATV71WD30N4 ATV71WD37N4
Electrical connection	Earth circuit terminal, connection capacity: 10 mm ² (AWG 6) Power supply terminal, connection capacity: 35 mm ² (AWG 0)

Complementary

Network number of phases	3 phases
Supply frequency	50...60 Hz
Voltage drop at rated load	6 %
Max current	1.65 x nominal current for 60 s
Tightening torque	Earth circuit : 1.2...1.4 N.m Power supply : 2.5...3 N.m
Height	171 mm
Width	126 mm
Depth	170 mm
Product weight	6.4 kg

Environment

IP degree of protection	IP20
relative humidity	0...95 %
ambient air temperature for operation	> 50...60 °C with current derating 2.2 % per °C -10...50 °C without current derating
ambient air temperature for storage	-40...65 °C
operating altitude	<= 1000 m without current derating 1000...3000 m with current derating 1 % per 100 m

Contractual warranty

Warranty period	18 months
-----------------	-----------