

VW3A7201

network braking unit - 7 kW - 400 V - for variable speed drive



Main

Product or component type	Network braking unit
Range compatibility	Altivar 71
[Us] rated supply voltage	400 V
Maximum current I _{rms}	11 A AC 13 A DC
Permanent braking power	7 kW
Maximum braking power	7 kW

Complementary

Supply circuit type	AC
Associated fuse rating	20 A at 660 V
Supply voltage limits	380...415 V
Network frequency	40...60 Hz +/- 10 %
Overload protection	1.2 x maximum current
Efficiency	97 %
Cos phi	1
Electrical connection	Bare wires connection M5 25 mm ² connection capacity
Height	500 mm
Width	270 mm
Depth	295 mm
Product weight	20 kg

Environment

IP degree of protection	IP20
relative humidity	Class F without condensation 5...85 %
ambient air temperature for operation	> 40...< 55 °C with current derating 3 % per °C 5...40 °C without current derating
ambient air temperature for storage	-25...55 °C
operating altitude	<= 1000 m without current derating 1000...4000 m with current derating 5 % per 1000 m

Contractual warranty

Warranty period	18 months
-----------------	-----------

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.